

CASE SPECIFICATIONS:

REFRIGERATION

DOORED LOAD: 1,875 BTU/hr

OPEN LOAD: 9,900 BTU/hr

TOTAL: 11,775 BTU/hr

COIL TEMP: 25°

LIQUID STUB: 3/8IN ODS

SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: 1.2A

LIGHTS: 3.6A


TOTAL: 4.8A

MCA: 15A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
		SCALE: 1:32	DRAWN BY: D HUNT		
		DATE: 5-12-16	CHECKED BY:		
		2DR / 6FT DF CMB LEFT			
DATE	REV.	DWG.	INCH		
REVISION	TOL:		DRAWING NUMBER P7183		