

CASE SPECIFICATIONS:

REFRIGERATION
 DOOR LOAD: 1,725 BTU/hr
 OPEN LOAD: 4,740 BTU/hr
 TOTAL LOAD: 6,465 BTU/hr
 COIL TEMP: 22° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .60A
 LIGHTS: 2.4A
 CONDENSATE PUMP: 1.0A
 TOTAL: 4.0A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 1HP COND. UNIT: 7.7A
 TOTAL: 14.9A
 MCA: 18.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



| | | | | | | | |
|------------------------|--|-------|--|---|--|------------------|--|
| AUTHORIZATION (PRINT): | | DATE: | |  börgeren systems | | DRAWN BY: D HUNT | |
| SIGNATURE: | | | | | | CHECKED BY: | |
| | | | | SCALE: 1:XX | | | |
| | | | | DATE: 5-24-17 | | | |
| | | | | 1 DR 3 1/4FT DF RIGHT CMB | | | |
| DATE | | REV. | | DIM: INCH | | DRAWING NUMBER | |
| REVISION | | TOL: | | | | P7342 | |