

**CASE SPECIFICATIONS:**

REFRIGERATION  
 DOORED LOAD: 1,900 BTU/hr  
 OPEN LOAD: 6,200 BTU/hr  
 TOTAL LOAD: 8,100 BTU/hr  
 COIL TEMP: 25°  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: 0.9A  
 LIGHTS: 2.4A  
 CONDENSATE PUMP: 1.0A  
 TOTAL: 4.3A  
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.  
 EVAP. PAN: 7.2A  
 1 1/4HP COND. UNIT: 9.2A  
 TOTAL: 16.4A  
 MCA: 19.4A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 <b>börgeren systems</b>	
SIGNATURE:					
				DATE: 3-15-18	CHECKED BY:
		1DR 2BAY GE OPEN 45 RIGHT			
DATE	REV.	DATE	INCH	DRAWING NUMBER	
REVISION	TOL:			P7512	