

CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 4,000 BTU/hr
 SUCTION TEMP: 25° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 1/2IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: .30A
 1/2HP COND. UNIT: 9.2A
 TOTAL: 9.5A
 MCA: 13.2A

SHIPPING WEIGHT: 694 LBS


EQUIPPED WITH CASTERS FOR PORTABILITY

CONDENSATE EVAP. SYSTEM INCLUDED



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börgeren systems		SCALE: 1:16		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 5-19-15		CHECKED BY:	
OPEN ISLAND OCTAGON									
DATE		REV.		DIM: INCH		DRAWING NUMBER		P6827	
REVISION		TOL:							