

CASE SPECIFICATIONS:


REFRIGERATION:
CASE LOAD: 2,050 BTU/hr
256 BTU/hr/ft
COIL TEMP: 17° F
LIQUID STUB: 3/8IN ODS
SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
LIGHTS: 3.6A
CONDENSATE PAN: 5.2A
1/2 HP COND. UNIT: 9.2A
TOTAL: 18.0A
MCA: 21.7A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börgeren systems		SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 8-25-16		CHECKED BY:	
				5-6-17 DRH		8FT SERVICE GRAVITY+ DFT			
		DATE		REV.		DIA:		INCH	
		REVISION				PQ30		DRAWING NUMBER	
								P7155	