

REMOVABLE AIR FILTER FOR AIR FLOW TO CONDENSING UNIT.

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 6,900 BTU/hr
 COIL TEMP: 22° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 208/230VAC, 60HZ, 1PH.
 EVAP. FANS: .22A
 LIGHTS: 1.2A
 EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.8A
 TOTAL: 15.42A
 MCA: 18.22A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börgeren systems		DRAWN BY: D HUNT	
SIGNATURE:						CHECKED BY:	
				SCALE: 1:24			
				DATE: 3-7-17			
				3FT END CAP			
DATE	REV.	DWG.	INCH			DRAWING NUMBER	
REVISION	TOL:					P7268	