



CASE SPECIFICATIONS:

REFRIGERATION:

CASE LOAD: 3,072 BTU/hr
 256 BTU/hr/ft
 COIL TEMP: 17° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 LIGHTS: 4.2A
 TOTAL: 4.2A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):
 DATE:

SIGNATURE:

		SCALE: 1:24	DRAWN BY: D HUNT
		DATE: 8-25-16	CHECKED BY:
5-6-17 DRH		12FT SERVICE GRAVITY+ DFT	
DATE	REV.	DWG. INCH	DRAWING NUMBER
REVISION		PQ30	P7156