





CASE SPECIFICATIONS:

ELECTRICAL 115VAC, 60HZ, 1PH.
 LIGHTS: 2.4A
 TOTAL: 2.4A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		börger systems		SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 9-14-17		CHECKED BY:	
				9-21-17		DRH		8' SELF SERV MD NON-REGRIG	
				DATE		REV		DIM: INCH	
				REVISION		TOL:		DRAWING NUMBER	
								P7398	