

CASE SPECIFICATIONS:

REFRIGERATION
 DOORED LOAD: 4,025 BTU/hr
 OPEN LOAD: 8,750 BTU/hr
 TOTAL LOAD: 12,775 BTU/hr
 SUCTION TEMP: 20-26° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.2A
 LIGHTS: 4.8A
 CONDENSATE PUMP: 1.0A
 TOTAL: 7.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.1A
 1 1/4HP COND. UNIT: 9.6A
 TOTAL: 22.9A
 MCA: 30.9A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börgeren systems	
SIGNATURE:					
				DATE: 8-21-18	CHECKED BY:
3DR/6FT OPEN RIGHT CMB					
DATE	REV.	DN:	INCH	DRAWING NUMBER	
REVISION	TOL:			P7604	