

CASE SPECIFICATIONS:

REFRIGERATION
 DOORED LOAD: 4,025 BTU/hr
 OPEN LOAD: 8,750 BTU/hr
 TOTAL LOAD: 12,775 BTU/hr
 SUCTION TEMP: 20-26° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.2A
 LIGHTS: 4.8A
 CONDENSATE PUMP: 1.0A
 TOTAL: 7.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.1A
 1 1/4HP COND. UNIT: 9.6A
 TOTAL: 22.9A
 MCA: 30.9A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



| | | | | | | | |
|------------------------|------|-------|------|---|--|------------------|--|
| AUTHORIZATION (PRINT): | | DATE: | |  börgeren systems | | DRAWN BY: D HUNT | |
| SIGNATURE: | | | | | | CHECKED BY: | |
| | | | | SCALE: 1:32 | | | |
| | | | | DATE: 8-21-18 | | | |
| 3DR/6FT OPEN LEFT CMB | | | | | | | |
| DATE | REV. | DN: | INCH | | | DRAWING NUMBER | |
| REVISION | TOL: | | | | | P7605 | |